


PANO 2"

WOODWORKS® GRILLE FORTÉ



CERTIFICATIONS & COMPLIANCE




FEATURES




PERFORMANCE

- Lengths coordinates with Woodworks® Grille ceiling panel
- Up to 109lm/W
- High performance opal cover
- Remote mountable LED driver
- Damp rated




WoodWorks® Grille Ceiling System Integration



REMOTE MOUNTING

Quick and easy electrical connection

REMOTE MOUNTING



Catalog Number Example

PANO2-WWG-BL-PS-OP-27K-C80-UNV-010V-0300LF-ST-04FT



A RANGE

PANO 2" PANO2

H VOLTAGE

120V / 277V UNV

B CEILING TYPE

WoodWorks® Grille WWG

please contact your Armstrong® ceilings rep for the Integrated Light Connection Clip for the specified ceiling type

I DIMMING

0-10V 1% 010V

Lutron EcoSystem LES1

Quantum, Vive, GRAFIK Eye, HomeWorks

Power over ethernet POEC

consult customer service for compatibility

Custom dimming XXXX

consult customer service for compatibility

C COLOR

White WH

Black BL

D POWER FEED LENGTH

4' standard integrated PS

10' medium remote option PM

30' long remote option PL

power feed distance denotes secondary wiring from detachable driver box to fixture; driver box comes with a 6 ft conduit for primary wiring

J OUTPUT LM/FT

300lm/ft 100% 0300LF

425lm/ft 100% 0425LF

600lm/ft 100% 0600LF

K CIRCUIT / EM

Single circuit *

* leave blank

EMB EM battery pack EMB

emergency battery pack only for

120/ 277V option

(90 minute emergency operation)

E LENS

HP opal cover OP

F CCT

2700K 27K

3000K 30K

3500K 35K

4000K 40K

Custom CCT XXX

L SHAPE / PATTERN

Linear / straight ST

M DIMENSIONS IN FT

4' fixture 04FT

6' fixture 06FT

8' fixture 08FT

fixture replaces full length of ceiling panel; please see table on next page and fixture length dimensions

G CRI

CRI > 80 C80

CRI > 90 C90

BASO

basolighting.com

CS-V01

03/2025


Technical data

	SIZE TYPE	LED COLOR TEMPERATURE	INPUT WATTS	DELIVERED LM TOTAL	LIGHT DISTRIBUTION	DELIVERED LUMEN DIRECT	OPTICAL EFFICIENCY	LUMINAIRE EFFICACY
PANO 2"								
e LED	8' opal	40 K	20.3 W	2200 lm	100 % down	2200 lm	70 %	108 lm/W
e ² LED	8' opal	40 K	31.2 W	3400 lm	100 % down	3400 lm	70 %	109 lm/W
e ²⁺ LED	8' opal	40 K	44.7 W	4800 lm	100 % down	4800 lm	70 %	107 lm/W

for 27 K, 30 K or 35 K multiply lm value by 0.96

WoodWorks® Grille Ceiling System Integration

(for more ceiling options, please see CEILING OPTIONS pages)



Available lengths for ceiling types

CEILING TYPE	2 FT	4 FT	6 FT	8 FT
WoodWorks® Grille Tegular 9/16	23.375"	47.375"	n/a	n/a
WoodWorks® Grille Tegular 15/16	23"	47"	n/a	n/a
WoodWorks® Grille Classic	23"	47"	71"	95"
WoodWorks® Grille Forte	*23"	47"	71"	95"
WoodWorks® Linear Solid Wood panels	*23"	*47"	*71"	95"
WoodWorks® Linear Veneered panels	*23"	*47"	*71"	95.25"

*Woodworks ceilings are not available in this length. Wood panels need to be cut in the field to fit this length.

INTEGRATED LIGHT CONNECTION CLIP

Armstrong® Ceilings Integrated Light Connection Clip

please contact your Armstrong Ceilings rep

visit
[armstrongceilings.com](https://armstrongceilings.com/linearlighting)
[/linearlighting](https://armstrongceilings.com/linearlighting)


WoodWorks® ceiling systems

BASO PANO is only approved for Armstrong® WoodWorks Grille Tegular 9/16, WoodWorks Grille Tegular 15/16, WoodWorks Grille, WoodWorks Linear Solid Wood panels and WoodWorks Linear Veneered panels ceiling systems. Refer to armstrongceilings.com for installation instructions related to the ceiling products.





PANO 2"

WWG - ARMSTRONG® WOODWORKS® GRILLE PANELS

WWG



WWG - ARMSTRONG® WOODWORKS® GRILLE PANELS cont'd



PANO mounting instructions

Get access to the PANO mounting instructions faster by scanning the QR code.

<https://www.basolighting.com/resources/mounting-instructions/pano>

